

ITT

Residential Water Systems

Goulds Pumps

DIAPHRAGM TANKS

HydroPro® Water System Tank




Goulds Pumps is a brand of ITT Corporation.

www.goulds.com

Engineered for life

FEATURES

- **Horizontal Models:** Feature a universal jet pump bracket and two (2) bolt-on, corrosion-resistant, high density polypropylene feet for installations with limited headspace, such as under mobile homes.
- **Deep Drawn Steel Shells:** Provide maximum material strength.
- **Union Models:** Include an SS union connection for installer convenience.
- **Inner Shell:** Prevents diaphragm from over-expanding.
- **Heavy Duty Diaphragm:** Made of finest quality butyl rubber. Separates air and water, maintains air charge.
- **Interior Tank Lining:**
 - Standard models feature durable polypropylene liner. Meets FDA requirements.
 - Mounted pump models feature fusion bonded polymeric lining. Meets FDA requirements.
- **Maximum Working Pressure:** 125 psi (except mounted pump models, 100 psi).
- **Temperature Rating:** Maximum 120° F.
- **Stainless Steel System Connection:** On all Stand, In-Line, Buried and Horizontal models.
- **Appliance Appearance Exterior Finish:** High durability exterior finish of tough, powder coat over a zinc phosphate surface treatment.
- **Heavy Duty Base:** Made of high density polypropylene.
- **Pre-charge:** All tanks charged to 38 PSI.



ITT

GOULDS PUMPS Residential Water Systems



Stand Models
V45 V140
V60 V200
V80 V250
V100 V260
V100S V350



Horizontal Models with Pump Mounting
V25H
V45H
V60H




**V80EX
Stand Model
with Base Extension**



In-Line Models
V6P V15P
V25P V45P



Mounted Pump Models
V60MP V60PST
V45MP V45PST



ITT

GOULDS PUMPS Residential Water Systems

	Std. Model No.	Union Model No.	Total Volume (Gals.)	Drawdown in Gals. at System Operating Pressure Range of			Maximum Drawdown Vol. (Gals.)	Pre-Charge PSI	System Connection	Dimensions		Shipping Weight	Height From Floor to Center of Base Opening
				20/40 PSIG	30/50 PSIG	40/60 PSIG				Diameter	Height		
Stand Models	V45	V45U	13.9	5.1	4.3	3.7	8.4	38	1" NPTF	15 ³ / ₈	24 ¹⁵ / ₁₆	23	3 ¹ / ₈
	V60	V60U	19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 ³ / ₈	32 ³ / ₈	34	
	V80	V80U	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 ³ / ₈	39 ⁹ / ₁₆	43	
	V80EX	V80EXU	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 ³ / ₈	42 ³ / ₈	43	7 ¹ / ₄
	V100	V100U	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	15 ³ / ₈	47 ¹ / ₄	52	3 ¹ / ₈
	V100S	V100SU	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	22	28	56	3 ³ / ₈
	V140	V140U	45.2	16.5	13.9	12.1	27.3	38	1 ¹ / ₄ " NPTF	22	36 ³ / ₁₆	64	
	V200	V200U	65.1	23.9	20.0	17.4	39.3	38	1 ¹ / ₄ " NPTF	22	48 ³ / ₈	89	
	V250	V250U	83.5	30.9	25.9	22.5	50.8	38	1 ¹ / ₄ " NPTF	26	46	116	3 ¹ / ₂
	V260	V260U	84.9	31.2	26.2	22.8	44.7	38	1 ¹ / ₄ " NPTF	22	60 ¹¹ / ₁₆	113	3 ³ / ₈
V350	V350U	115.9	42.9	35.9	31.3	70.5	38	1 ¹ / ₄ " NPTF	26	61 ¹ / ₁₆	161	3 ¹ / ₂	
Mounted Pump Models*	V45MP		13.9	5.1	4.3	3.7	8.4	38	3/4" Pipe	15 ³ / ₈	25 ¹ / ₁₆	28	
	V60MP		19.9	7.3	6.1	5.3	12.1	38	3/4" Pipe	15 ³ / ₈	33 ¹ / ₈	40	
	V45PST		13.9	5.1	4.3	3.7	8.4	38	3/4" Pipe	15 ³ / ₈	25 ¹ / ₁₆	28	
	V60PST		19.9	7.3	6.1	5.3	12.1	38	3/4" Pipe	15 ³ / ₈	33 ¹ / ₈	40	
Buried Models	V45B		13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	21 ¹ / ₁₆	23	
	V60B		19.9	7.3	6.1	5.3	12.1	38	1" NPTM	15 ³ / ₈	28 ¹ / ₂	33	
	V140B		45.2	16.5	13.9	12.1	27.3	38	1 ¹ / ₄ " NPTM	22	32 ³ / ₁₆	63	
	V200B		65.1	23.9	20.0	17.4	39.3	38	1 ¹ / ₄ " NPTM	22	44 ¹ / ₄	87	
In-Line Models	V6P		2.0	0.7	0.6	0.5	1.2	38	3/4" NPTM	8	11 ¹⁵ / ₁₆	8	
	V15P		4.5	1.7	1.4	1.2	2.7	38	3/4" NPTM	11	13 ¹⁵ / ₁₆	12	
	V25P		8.2	3.1	2.6	2.2	4.5	38	3/4" NPTM	11	23 ¹ / ₁₆	21	
	V45P		13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	21 ¹ / ₁₆	24	
Horizontal Models w/ Bracket	V25H		8.2	3.1	2.6	2.2	4.5	38	3/4" NPTM	11	24 ⁹ / ₁₆	23	
	V45H		13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	22 ⁹ / ₁₆	26	
	V60H		19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 ³ / ₈	33 ³ / ₈	36	

NOTES:

* Compatible with only certain Goulds jet pumps.

P = Pipe mounted
MP = Mounted pump

EX = With base extension
PST = Pump system tank

B = Buried
H = Horizontal with bracket

U = Union Connection

(All dimensions are in inches and weight in lbs. Do not use for construction purposes.)

ACCESSORIES



■ **AW39 Bracket:**
Universal pump mounting bracket for use on all stand model tanks.



■ **AWT1 Base Extension:**
For use on 1⁵/₈" models. Provides 4¹/₈" base elevation. Supplied in quantities of six (6) per carton.

Order No.	Description	Wt. (bs.)
AW39	Universal Jet Pump Bracket	2
AWT1	Tank Base Extension (Qty. 6)	5